

GEVORGIAN, S. et al.
Serial No. 10/781,930

Atty Dkt: 4127-13
Art Unit: 2817

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) A tunable resonating arrangement ~~comprising~~
comprising:
a resonator apparatus which provides a two pole filter,
input/output coupling means for coupling electromagnetic energy into/out of the
resonator apparatus, and
a tuning device for application of a biasing voltage/electric field to the resonator
apparatus,
~~characterized in~~
that wherein the resonator apparatus comprises:
a first resonator, and
a second resonator,
that wherein said first resonator is non-tunable,
that wherein said second resonator is tunable and comprises a ferroelectric
substrate,
a ground plane for separating that said first and second resonators are
separated by a, the ground plane which is being common for said first and second
resonators, ~~that~~
coupling means ~~are provided for providing coupling between said first and~~
second resonators, ~~and in that~~
wherein for tuning of the resonator apparatus, the biasing voltage/electric
field is applied to the second resonator.

2. (Currently Amended) A tunable resonating arrangement according to claim 1,

GEVORGIAN, S. et al.
Serial No. 10/781,930

Atty Dkt: 4127-13
Art Unit: 2817

~~characterized in~~
that wherein the first resonator, is a disk resonator, or a ~~parallel-parallel~~ plate resonator.

3. (Currently Amended) A tunable resonating arrangement according to claim 1,
~~characterized in~~
that wherein the second resonator is a disk resonator, or a ~~parallel-parallel~~ plate resonator.

4. (Currently Amended) A tunable resonating arrangement according to claim 2,
~~characterized in~~
that wherein the first resonator comprises a dielectric substrate, the electric permittivity of which substantially does not vary with applied biasing voltage, which is disposed between a first resonator first electrode and a first resonator second electrode, and in that the first resonator second electrode ~~of the first resonator~~ forms the ground plane.

5. (Currently Amended) A tunable resonating arrangement according to claim 4,
~~characterized in~~
that wherein the dielectric substrate of the first resonator comprises LaAlO₃, MgO, NdGaO₃, Al₂O₃, sapphire ~~or a material with similar properties~~.

6. (Currently Amended) A tunable resonating arrangement according to claim 4,
~~characterized in~~
that wherein the first resonator has a high quality factor (Q), e-gand preferably exceeding approximately 10⁵ [-] to 5·10⁵.

7. (Currently Amended) A tunable resonating arrangement according to claim 4,

GEVORGIAN, S. et al.
Serial No. 10/781,930

Atty Dkt: 4127-13
Art Unit: 2817

~~characterized in~~

~~that wherein the second resonator comprises a tunable ferroelectric substrate and, a second resonator first electrode, and a second resonator second electrode, and in that the second resonator second electrode of the second resonator forms the common ground plane, and thus the second resonator second electrode is the same as the first resonator second electrode of the first resonator.~~

8. (Currently Amended) A tunable resonating arrangement according to claim 7,

~~characterized in~~

~~that wherein the ferroelectric substrate of the second resonator comprises SrTiO₃, KTaO₃, or BaSTO₃ or a material with similar properties.~~

9. (Currently Amended) A tunable resonating arrangement according to claim 4,

~~characterized in~~

~~that the first and second electrodes, i.e. the first electrodes and the common ground plane, consist of normal, wherein the electrodes comprise a non-superconducting metal, e.g. Au, Ag, Cu.~~

10. (Currently Amended) A tunable resonating arrangement according to claim 4,

~~characterized in~~

~~that the first and second electrodes, i.e. the first electrodes and the common ground plane, consist of wherein the electrodes comprise a superconducting material.~~

11. (Currently Amended) A tunable resonating arrangement according to claim 4,

~~characterized in~~

~~that the first and second electrodes, i.e. the first electrodes and the common ground plane consist of wherein the electrodes comprise a high temperature superconducting material (HTS), e.g. YBCO.~~

GEVORGIAN, S. et al.
Serial No. 10/781,930

Atty Dkt: 4127-13
Art Unit: 2817

12. (Currently Amended) A tunable resonating arrangement according to claim 1,
~~characterized in~~
~~that wherein~~ upon the application of a ~~tuning~~ (biasing) voltage to said second
resonator, electromagnetic energy (EM) ~~will be~~ is redistributed between the second and
first resonators via the coupling means.

13. (Currently Amended) A tunable resonating arrangement according to claim 12,
~~characterized in~~
~~that the wherein~~ the redistribution of electromagnetic energy depends ~~on~~ is a
function of -the biasing voltage.

14. (Original) A tunable resonating arrangement according to claim 13,
~~characterized in~~
~~that wherein~~ the transfer of electromagnetic energy from the second resonator to
the first resonator increases with an increasing biasing voltage.

15. (Currently Amended) A tunable resonating arrangement according to claim 10,
~~characterized in~~
~~that wherein~~ the resonating frequency and the loss tangent of the second resonator
increase with the application of an increasing biasing voltage, and ~~in that also wherein~~ the
transfer of electromagnetic energy from the second to the first resonator is increased,
automatically compensating for the increased loss tangent of the second resonator by
reducing ~~the influence~~ thereof on the coupled resonator apparatus.

16. (Original) A tunable resonating arrangement according to claim 1,
~~characterized in~~
~~that wherein~~ the first and second resonators comprise thin film substrates.

GEVORGLIAN, S. et al.
Serial No. 10/781,930

Atty Dkt: 4127-13
Art Unit: 2817

17. (Currently Amended) A tunable resonating arrangement according to claim 1,
~~characterized in~~
~~that it comprises~~ further comprising at least two resonator apparatuses, and in that
the common ground plane is common for the at least two resonator apparatuses which
form a tunable filter.

18. (Currently Amended) A tunable resonating arrangement according to claim 1,
~~characterized in~~
~~that wherein~~ the coupling means comprises, for each resonator apparatus, a slot or
an aperture in the common ground plane.

19. (Currently Amended) A tunable resonating arrangement according to claim 1,
~~characterized in~~
~~that wherein~~ each resonator is circular, square shaped, rectangular or ellipsoidal.

20. (Currently Amended) A tunable resonating arrangement according to claim 19,
~~characterized in~~
~~that it comprises~~ wherein the arrangement comprises a dual mode resonator
apparatus, and in that wherein each resonator comprises a protrusion, a cut-out, or a
perturbation to provide for dual mode operation.

21. (Currently Amended) A tunable resonator apparatus,
~~characterized in~~
~~that it comprises~~ comprising:
a first resonator;
~~and a second resonator;~~

GEVORGIAN, S. et al.
Serial No. 10/781,930

Atty Dkt: 4127-13
Art Unit: 2817

~~that said first resonator is being non-tunable;~~ ~~that said second resonator is being a~~
tunable ferroelectric resonator, the first resonator and the second resonator forming a two
pole filter; ~~that~~

a ground plane for separating said first and second resonators ~~are separated by a,~~
the ground plane which is being common for said first and second resonators; ~~that;~~

coupling means are provided for providing coupling between said first resonator
and said second resonators; ~~and~~

in that wherein for tuning of the resonator apparatus, a biasing voltage is applied to
the second resonator.

22. (Currently Amended) A tunable resonator apparatus according to claim 21,

~~characterized in~~

~~that wherein~~ the first resonator and the second resonator comprise parallel-parallel
plate resonators, that the common ground plane is formed by a second electrode plate of
the first resonator and of a second electrode of the second resonator, and in that wherein
the coupling means comprises a slot or an aperture in the common ground plane.

23. (Currently Amended) A tunable resonator apparatus according to claim 22,

~~characterized in~~

~~that wherein~~ the first resonator comprises a substrate, bulk or thin film, comprised
of LaAlO_3 , MgO , NdGaO_3 , Al_2O_3 , or sapphire, ~~or a material with similar properties,~~ and
in that

wherein the second resonator comprises a substrate, bulk or thin film, comprised of
 SrTiO_3 , or KTaO_3 , ~~or a material with similar properties,~~

wherein the electrode plates comprising comprise normal metal, or [()] high
temperature [()] superconductors.

24. (Currently Amended) A method of tuning a resonator apparatus,

GEVORGIAN, S. et al.
Serial No. 10/781,930

Atty Dkt: 4127-13
Art Unit: 2817

~~characterized in~~
~~that it comprises the steps of comprising:~~
[(-)] providing a first, non-tunable, resonator,
[(-)] providing a second tunable resonator,
~~separating such that the first and second resonators are separated by and share a~~
common ground plane,

[(-)] providing coupling means in said common ground plane such that the first and second resonators become coupled, allowing transfer of electromagnetic energy between the first and second resonators,

[(-)] applying a biasing/tuning voltage to said second resonator ~~increasing for~~
~~changing~~ the resonating frequency, the loss tangent of the second resonator, and the transfer of electromagnetic energy to the first resonator,

[(-)] optimizing ~~the application of the biasing voltage such that the influence of the~~
increased loss tangent in the first resonator, on the coupled resonator apparatus, will be compensated for, by an increased transfer of electromagnetic energy to the first resonator.

25.(original) The method of claim 24,

~~characterized in~~
~~that wherein~~ the first resonator and the second resonator comprise disk or parallel
~~parallel~~ plate resonators, ~~that wherein~~ the common ground plane is formed by a second
electrode plate of the first resonator and of a second electrode of the second resonator,
~~and in that wherein~~ the coupling means comprises a slot or an aperture in the common
ground plane.

26. (Currently Amended) The method of claim 24,

~~characterized in~~

GEVORGIAN, S. et al.
Serial No. 10/781,930

Atty Dkt: 4127-13
Art Unit: 2817

~~that wherein~~ the first resonator comprises a substrate, ~~bulk or thin film, comprised~~
of LaAlO_3 , MgO , NdGaO_3 , Al_2O_3 , ~~or sapphire, or a material with similar properties, and~~
~~in that~~

~~wherein~~ the second resonator comprises a substrate, ~~bulk or thin film, comprised~~ of
 SrTiO_3 , ~~or~~ KTaO_3 , ~~or a material with similar properties,~~

~~wherein~~ the electrode plates ~~comprising~~ comprise normal metal, or ~~[[C]]~~ high
temperature~~[[D]]~~ superconductors.

27. (Currently Amended) The method of claim 2426,

~~characterized in~~

~~that it comprises the step of~~ further comprising:

~~[[-]]~~ coupling two or more resonator apparatuses such that a filter is provided,

~~[[-]]~~ optimizing the coupling between the respective first and second resonator
such that the increasing loss factor produced by an increased biasing voltage, ~~in the~~
~~ferroelectric substrates, can be~~ is reduced.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.